

BLANK PAGE



Indian Standard SPECIFICATION FOR HOSPITAL RUBBER SHEETING WITHOUT REINFORCING FABRIC

UDC 678·4-41:615·478·275



© Copyright 1976

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

December 1976

AMENDMENT NO. 1 JANUARY 1990 TO

IS: 8164 - 1976 SPECIFICATION FOR HOSPITAL RUBI EETING WITHOUT REINFORCING FABRIC

(Page 4, clause 2.2) — Add the following in the end:

The sheeting shall have a minimum thickness of 1 mm and shall be uniform in thickness.'

[Page 5, Table 1, St No. (vi), col 5] — Substitute the following for the existing matter:

'IS: 7016 (Part VII) - 1973°, Using Low Pressure Method',

(Page 6, clause 2.4) — Add the following new clause after 2.4:

'2.5 Preservation — The sheeting shall be properly dusted with a suitable preservative to avoid stickiness. French chalk is a suitable preservative. Other treatment may be given if agreed to between the purchaser and the supplier.'

(PCDC 13)	
	Printed at Printwell Printers, Delhi, India

AMENDMENT NO. 2 OCTOBER 2008 TO IS 8164: 1976 SPECIFICATION FOR HOSPITAL RUBBER SHEETING WITHOUT REINFORCING FABRIC

[Page 4, clause 2.3, Table 1, Sl No (III), col 2] — Substitute 'Min' for 'Max'

(PCD 13)

Reprography Unit, BIS, New Delhi, India

Indian Standard

SPECIFICATION FOR HOSPITAL RUBBER SHEETING WITHOUT REINFORCING FABRIC

Rubber Products Sectional Committee, CDC 6

Representing Chairman DR D. BANERJEE Escon Consultants Pvt Ltd, Calcutta Members Ministry of Defence (R & D) SHRI M L. BAHRANI SHRI ANIL AGARWAL (Alternate) Ministry of Defence (DGI) SHRI A. K. BANDYOPADHAYA SHRI M. KUMARAN (Alternate) SHRI M. BANERJEE National Rubber Manufacturers Ltd, Calcutta SHRIJ. CHATTERJEE (Alternate) Directorate General of Supplies & Disposals, New SHRI A. T. BASAK Delhi SHRI S. K. BOSE National Test House, Calcutta SHRI A. GHOSH (Alternate) Bayer (India) Ltd, Bombay Dr S N. CHAKRAVARTY SHRI R. R. PANDIT (Alternate) Alkalı & Chemical Corporation of India Ltd, Calcutta SHRI D. K. CHATTERJEE DR S K. Roy (Alternate) SHRI S. S. CHOPRA Export Inspection Council of India, Calcutta SHRI K. M. BIJLI (Alternate) All India Rubber Industries' Association, Bombay SHRI W. G. DESAL SHRI K. R. SENGUPTA (Alternate) SHRIK N. GANESH Indian Petrochemicals Corporation Ltd, Vadodara SHRI S. B. GANGULI Dunlop India Ltd, Calcutta SHRIP. N.S MYER (Alternate) Madras Rubber Factory Ltd, Madras SHRI A. GEORGE JOHN Shri K. J. Abraham (Alternate) Shri G. C. Jain Shri R C. Jhingan Hındustan Steel Ltd, Ranchı Indian Oil Corporation Ltd, Bombay Cosmos India Rubber Works Pvt Ltd, Bombay SHRI LALIT MOHAN JAMNADAS SHRI PULIN L. KINARIWALA (Alternate) Lathia Rubber Manufacturing Co Pvt Ltd, Bombay Shri S. V. Lathia SHRI D. P. LATHIA (Alternate) Dr S. P. Manik Railway Board (Ministry of Railways) SHRI D. N. V. CHELLAM (Alternate) Rubber Board, Kottayam DR C. K. N. NAIR

(Continued on page 2)

© Copyright 1976 INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS:	8164 - 1976	
(Go)	ntinued from page 1)	
	Members	Representing
	i S. C. Nandy Shri Sunil Sarkar (<i>Alternate</i>)	Bata India Ltd, Calcutta
SHR	M. M PATEL	Synthetics & chemicals Ltd, Bombay
	N. V. C RAO	Directorate General of Technical Development, New Delhi
	Shri G. R. Inamdar (<i>Alternate</i> : V. R. Rao) Sundaram Industries Pvt Ltd, Madurai
	SHRI K. C. MADHUSUDHANAN (
	R. C. SYED	Indian Rubber Manufacturers' Research Association, Bombay
	D D Talwalkar	All India Automobile & Ancillary Industries Associa- tion, Bombay
	HRIK. M. KHALADKAR (Alteri	nate)
	G. M. SAXENA, irector (Chem.)	Director General, ISI (Ex-officio Member)
		Secretary
	Si	hri Satish Chander
	Deput	y Director (Chem), ISI
!- .	Medical Rubber	Goods Subcommittee, CDC 6:7
	i M. Banerjeë Shri J. Chatterjeë (<i>Alternate</i>)	National Rubber Manufacturers Ltd, Calcutta
SHR	A Bose SHRITTA (Alternate)	Bengal Water Proof Works (1940) Ltd, Calcutta
SHR	S. K. Bose Shri S. P. Mullick (Alternate)	National Test House, Calcutta
SHRI	R N CHAKRAVARTY SHRI A. CHAUDHURI (Alternate)	Indian Oxygen Ltd, Calcutta
Dr l	P. C. Kapur S. V. Kulkarni	Directorate General of Health Services, New Delhi Haffkine Institute, Bombay
SHR	SHRI R. S. KARBHARI (Alternate M. KUMARAN	Ministry of Defence (DGI)
Maj	SHRIB C. SEN (Alternate) V. G. LAGHATE	Directorate General of Armed Forces Medical Services, New Delhi
Shr	LT-COL M. K. BAGCHI (Alterna, S. V. LATHIA	te) Lathia Rubber Manufacturing Co Pvt Ltd, Bombay
SHR	SHRI D. P. LATHIA (Alternate) M. M. PATEL SHRI N. M. REGE (Alternate)	Synthetics & Chemicals Ltd, Bombay
SHR	MANUBHAI M. PATEL SHRI K. C. SHAH (Alternate)	Rubberex Industries Pvt Ltd, Bombay
SHR	IM. N. PATHAK	Associated Rubber Industries Ltd, Bhavnagar Swastik Rubber Products Ltd, Pune
	IV. D. PENDSE Shri K. D. Dighe (Alternate)	DWASHE RUDGET FLOUDERS LEG, FURE
Dr I	N. V. C RAO	Directorate General of Technical Development, New Delhi
•	Sunt C. R. INAMENAD (Alternate)	1

SHRI G R. INAMDAR (Alternate)

Indian Standard SPECIFICATION FOR HOSPITAL RUBBER SHEETING WITHOUT REINFORCING FABRIC

0. FOREWORD

- **0.1** This Indian Standard was adopted by the Indian Standards Institution on 28 June 1976, after the draft finalized by the Rubber Products Sectional Committee had been approved by the Chemical Division Council.
- **0.2** Rubber sheetings both with and without reinforcing fabric are commonly used in hospitals. Rubber sheetings having cotton or synthetic fabric coated on both sides with rubber are covered in IS 4135-1974* The present standard covers only the rubber sheeting without any reinforcing fabric.
- **0.3** This standard contains clauses **2.1.2**, **2.4** and **3.1** which call for agreement between the purchaser and the supplier
- **0.4** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960†. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes the requirements, and methods of sampling and test for plain rubber sheetings without any reinforcing fabric, for use in hospitals.

2. REQUIREMENTS

2.1 Materials — The sheeting shall be made from natural rubber or suitable synthetic rubber or combination thereof, compounded with necessary ingredients so that the rubber sheeting conforms to all the requirements of the specification.

^{*}Specification for hospital rubber sheetings (first revision)

[†]Rules for rounding off numerical values (revised)

- 2.1.1 The rubber sheeting shall not contain any substances injurious to human body or having any deleterious effect on the rubber polymer.
- 2.1.2 The colour of the rubber sheeting shall be as agreed to between the purchaser and the supplier.
- 2.2 Workmanship and Finish The rubber sheeting shall be smooth, soft and pliable. It shall be free from pinholes, cuts, embedded foreign matter, surface irregularities, objectionable stains or odour. The workmanship shall be consistent with good manufacturing practice.
- 2.3 The rubber sheeting shall also conform to the requirements given in Table 1.

TABLE 1 REQUIREMENTS FOR HOSPITAL RUBBER SHEETING WITHOUT REINFORCING FABRIC

SL	CHARACTERISTIC	Requirement	Метно	D of Test, Ref to
No.			Appendix	Indian Standard
(1)	(2)	(3)	(4)	(5)
(۱)	Mass, g/m ²	800 to 1000	_	IS · 7016 (Part I)-
ii)	Tensile strength, MN/m ² (approx kgf/cm ²), Min	14 (140)		IS: 3400 (Part I)- 1965†, The thick- ness of the test specimen shall be same as single thickness of the product
iu)	Elongation at break, percent, Max	350	~	do
1v)	Tension set at 250 percent elongation and 15 min recovery time, percent, Max	10		IS · 3400 (Part XIII)- 1972‡, Using strip test pieces with enlarged ends and of thickness same as single thick- ness of the pro- duct
v)	Accelerated ageing at 70°C for 168 hours in air oven.			IS: 3400 (Part IV)- 1965§
	a) Change in tensile strength from original, percent, Max	+10 25		

Methods of test for coated and treated fabrics: Part I Determination of roll characteristics.

(Continued)

[†]Methods of test for vulcanized rubbers: Part I Tensile stress-strain properties

[‡]Methods of test for vulcanized rubbers: Part XIII Tension set

Methods of test for vulcanized rubbers Part IV Accelerated ageing

TABLE 1 REQUIREMENTS FOR HOSPITAL RUBBER SHEETING WITHOUT REINFORCING FABRIC—Contd

SL No.	Characteristic	Requirement	METHOD OF TEST, REF TO		
140.			Appendix	Indian Standard	
(1)	(2)	(3)	(4)	(5)	
	b) Change in elongation at break from original, percent, Max	+ 0 25			
vi)	Waterproofness under 300 mm head of water	There shall be no percolation or wet patches on the surface in contact with air	_	IS - 7016(Part VII)- 1973*	
vII)	Colour fastness to washing	Rating shall not be less than 5	-	IS: 765-1966†	
vii1)	Colour fastness to light	Rating shall not be less than 3	_	IS: 2454-1967 #	
ıx)	Autoclaving test:		A	~	
	a) Change in tensile strength from original, percent, Max	+10 25			
	b) Change in clongation at break from original, percent, Max	+10 15			
x)	Reaction of aqueous extract	The extract shall neither be acidic to methyl orange nor alkaline to phenolphthalein	В	~	
x1)	Resistance to detergents and disinfectants	The test pieces shall not show any tackiness or other apparent deter- ioration	С	~	

^{*}Methods of test for coated and treated fabrics. Part VII Determination of water-proofness.

[†]Methods for determination of colour fastness of textile materials to washing: test 4 (revised).

 $^{$\}mathbb{R}^{n}$$ Method for determination of colour fastness of textile materials to artificial light (xenon lamp).

2.4 Length and Width — The length of the rubber sheeting shall not be less than 20 metres unless otherwise agreed to between the purchaser and the supplier. Similarly unless otherwise agreed to, the width of the sheeting shall be 90 ± 1 cm. The length and the width shall be determined in accordance with the method given in IS: 7016 (Part I)-1973*.

3. PACKING AND MARKING

- **3.1 Packing** The rubber sheetings shall be packed as agreed to between the purchaser and the supplier.
- **3.2 Marking** Each piece of rubber sheeting shall be indelibly and clearly marked at one end with:
 - a) Manufacturer's name or trade-mark, if any;
 - b) Month and year of manufacture and batch number; and
 - c) Length and width.
- 3.2.1 The rubber sheeting may also be marked with the ISI Certification Mark.

Note — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

4. SAMPLING

4.1 For the purpose of ascertaining conformity of the sheeting in a consignment, the scale of sampling and criterion for conformity shall be as prescribed in Appendix D

APPENDIX A

[Table 1, Item (ix)]

AUTOCLAVING TEST

A-1. PROCEDURE

A-1.1 Subject dumbbell test pieces cut from the sample to steam pressure of 0·1 MN/m² (approx 1 kgf/cm²) for 20 minutes in an autoclave after

^{*}Methods of test for coated and treated fabrics' Part I Determination of roll characteristics.

removal of air. Take out the test pieces from the autoclave and expose them to air at room temperature for 2 hours. Repeat the autoclaving process after which blot out the adhering water from the test pieces and condition them for 24 hours in air at $27 \pm 2^{\circ}$ C and 65 ± 5 percent relative humidity. The test pieces are then subjected to tensile and elongation at break test according to IS: 3400 (Part I)-1965*.

APPENDIX B

[Table 1, Item (x)]

REACTION OF AQUEOUS EXTRACT

B-1. PROCEDURE

B-1.1 Weigh 10 g of the sample, cut into small pieces appoximately 3 mm² in area, into a chemically resistant glass flask and add 300 ml of water. Fit the flask with a water-cooled reflux condenser with ground-glass connection and heat the water to boiling point. Continue boiling for half an hour. Detach the flask from the condenser, cover immediately to prevent any possible contamination and cool the contents to room temperature. Check the reaction of aqueous extract to methyl orange and phenolphthalein.

APPENDIX C

[Table 1, Item (xi)]

TEST FOR RESISTANCE TO DETERGENTS AND DISINFECTANTS

C-1. REAGENTS

- C-1.1 Phenol saturated aqueous solution of phenol (see IS . 538-1968).
- C-1.2 Anmonia Solution relative density 0.9 (see IS: 799-19551).
- C-1.3 Soap Solution 5 percent aqueous solution of soap (m/v) conforming to Type 1 of IS: 285-1974§

C-2. PROCEDURE

C-2.1 Take three samples of the finished sheeting. Immerse one in each of the specified reagents for the length of time and temperature stated

[•] Methods of test for vulcanized rubbers: Part I Tensile stress-strain properties.

[†]Specification for phenol (carbolic acid) (first revision).

[‡]Specification for ammonia, liquor, technical.

^{\$}Specification for laundry soaps (second revision).

below. After immersion, examine the pieces visually.

Immersion Medium	Time, Min	Temperature
Phenol solution	15	$27 \pm 2^{\circ}C$
Ammonia solution	30	$27 \pm 2^{\circ}C$
Soap solution	10	Boiling temperature

APPENDIX D

(*Clause* 4.1)

SAMPLING OF HOSPITAL RUBBER SHEETING WITHOUT REINFORCING FABRIC

D-1. SCALE OF SAMPLING

D-1.1 Lot — All the hospital rubber sheetings in a single consignment belonging to a single batch of manufacture shall be grouped together to constitute a lot.

D-1.2 Samples shall be tested separately for each lot for ascertaining the conformity of the lot to the requirements of this specification. The number of samples to be selected for this purpose shall be in accordance with Table 2.

TABLE 2 SCALE OF SAMPLING

No. of Rolls in a Lot	No. of Rolls to be Selected
(1)	(2)
2 to 8	2
9,, 25	3
26 ,, 100	5
101 ,, 300	8
301 ,, 1 000	13
1001 and above	20

D-1.3 The selection of rolls from a lot shall be done at random. To ensure the randomness of selection, random number tables (see 1S: 4905-1968*) shall be used. In case random number tables are not available the following procedure may be adopted:

Starting from any roll in the lot, count them in one order as 1, 2, 3,, etc, up to r and so on, where r is the integral part of N/n, N being the number of rolls in the lot and n the number of rolls to be selected. Every rth roll shall be taken to constitute the sample.

^{*}Methods for random sampling.

D-2. NUMBER OF TESTS AND CRITERION FOR CONFORMITY

- **D-2.1** Every one of the rolls selected in **D-1.2** shall be examined for all the requirements of this specification individually. For this purpose, from each roll a full width piece of 450 mm in length shall be cut leaving at least half a metre from the end. The test pieces for all the tests shall be taken from this piece.
- **D-2.2** The lot shall be considered to satisfy the requirements of this specification if none of the rolls selected and tested fails in any of the requirements of this specification.

INDIAN STANDARDS

ON

MEDICAL RUBBER PRODUCTS

	IS-	
	1867-1975	Rubber hot water bottles (first revision)
	356 5-1966	Rubber teats for feeding bottles
	3 692-1975	Rubber closures (pharmaceutical) (first revision)
	3701-1966	Rubber protective sheaths (condoms)
	38 67-19 6 6	Rubber ice bags
	4135-1974	Hospital rubber sheetings (first revision)
	4148-1967	Surgical rubber gloves
	4149-1967	Post-mortem rubber gloves
	5680-1969	Rubber tubing for medical use
	5 783-197 0	Rubber ward-dressing and porters' gloves
	6058-1970	Rubber components for transfusion fluid bottles
	6407-1971	Rubber aprons for hospital use
	7352-1974	X-ray lead-rubber protective aprons
	7523-1974	Rubber catheter (urinary)
	8164-1976	Hospital rubber sheeting without reinforcing fabric
٠,	• ·	

-- PUBLICATIONS OF INDIAN STANDARDS INSTITUTION INDIAN STANDARDS

Over 8 500 Indian Standards covering various subjects have been issued, so far. Of these standards belonging to the Chemical Group fall under the following

Acids Adhesives Alcohols and aited products Alkalis Brushware Cermicware, enamelware and laboratory porceiain Chemical hazards and safety Chemicais, morganic (miscellaneous) Chemica's, organic (miscellaneous) Coal and coke Coal carbonization products Coated fabrics Cosmetics and toilet goods Drying oils Dye Intermediates Electroplating chemicals Explosive and pyrotechnic materials Fertilizers Fillers, stoppers and puttles Footwear Glass and glassware industrial gases inks and allied products Laboratory glassware thermometers and related apparatus Lac and lac products Leather, leather goods and leather dressings

Linters and ailied products Lubricants and related products Oil pastes Olls & fats, oleaginous seeds and fruits Painters' materials (miscellaneous) Paper and its products Paper and pulp board packaging materials Perfumery materials, natural and synthetic Petroleum and petroleum producte Photographic chemicals Pigments and extenders Plastics **Polishes** Printing lake Ready mixed paints and enamels Rubber and rubber products Scaps and other surface active agents Tanning materials allied products Thormal insulation materials Thinners and solvents Varalshes and lacquers Water and water treatment Water based paints Unclassified

OTHER PUBLICATIONS

ISI Bulletin (Published Every	y Month)					
Single Copy					Rs	4.00
Annual Subscription	, .	***			Rs	36160
Standards: Monthly Additions	;					
Single Copy	,			***	Re	0 30
Annual Subscription		***	***	***	Rs	3.00
Annual Reports (from 1948-49	Onwards)			Rs '	2 00 1	0 6 00
ISI Handbook, 1975	•	•		••	Rs	$30.\overline{00}$

INDIAN STANDARDS INSTITUTION

INDIAN STANDARDS INSTITUTION				
Manak Bhavan, 9 Bahadur Shah Zafar Telephone: 27 01 31 (20 lines)	Marg, NEW DELHI 11000 Telegrams: Man			
Regional Offices. Western: Novelty Chambers, Grant Road Eastern: 5 Chowringhee Approach Southern: C.I.T. Campus, Adyar	BOMBAY 400007 CALCUTTA 700072 MADRAS 600020	Telephone 37 97 29 23-08 02 41 24 42		
Branch Offices: 'Pushpak', Nurmohamed Shaikh Marg, Khanpur 'F' Block, Unity Bldg, Narasımharaja Square Ahımsa Bldg, SCO 82-83, Sector 17C 5-8-56,57 Nampally Station Road 117/418 B Sarvodaya Nagar B.C.I. Bidg (3rd Floor), Gandhi Maidan East Hantex Bldg (2nd Floor), Riy Station Road	AHMADABAD 380001 BANGALORE 560002 CHANDIGARH 160017 HYDERABAD 500001 KANPUR 208005 PATNA 800004 TRIVANDRUM 695001	2 03 91 2 76 49 2 83 20 4 57 11 82 72 5 36 55 32 27		

Printed at Delhi Printers, New Delhi, India